

Ratings @ 0.8 PF		Prime Rating	Stand by Rating	Dimensions	
Voltage* ¹	Frequency* ²	IMG 11* ³	IMG 12* ⁴	Length	1400 mm
220/380 V	60 Hz	10.9 kVA	12.1 kVA	Width	610 mm
127/220 V	60 Hz	10.7 kVA	12.1 kVA	Height	1020 mm
277/480 V	60 Hz	10.7 kVA	12.1 kVA	Weight	285 Kg

The above ratings represent the generating set capability guaranteed within $\pm 3\%$ at the reference conditions equivalent to those specified in ISO 8528/1 standard.

Notes

1. The applicable voltage range is 220V, 380V to 480V for 60Hz applications. For other voltages, please consult factory .

2. This generating set is of fixed speed of 1800 rpm.

3. IMG1150 is the prime power rating of the generating set is when a variable load and unlimited hour usage are applied with an average load factor of 80% of the prime rating over each 24-hour period. Noting that a 10% overload is permitted for 1 hour in every 12-hour operation.

4. IMG1275S is the standby power rating of the generating set is when a variable load limited to an annual usage up to 500 hours is applied, with 300 hours of which may be continuous running. Noting that no overload is permitted.

5. This rating level at voltage 220/380 is achieved when upsizing alternator to LSA50.2M6

Engine Technical Data

Make & Model	KUBOTA D1105-E2-BG		
Cylinders & Arrangement	3 - vertical in-line		
Bore & Stroke (mm)	78 x 78.4		
Induction system	Naturally aspirated		
Combustion	Indirect injection		
Cycle	4 stroke		
Compression ratio	24		
Cooling System	Water cooled		
Displacement	1.123 liters		
Lube oil capacity	5.1 liters Max		
Coolant capacity	5.1 liters		
Standard governor (Optional)	Mechanical +/-5% (Electronic)		
Engine Speed	1800 rpm		
Fuel Consumption (L/H) @ 100% Load	2.6	@ 50% Load	1.3
Fuel Consumption (L/H) @ 75% Load	1.95	@ 25% Load	0.65
Radiator Cooling Air Flow (m3/s)	0.44		
Emissions regulations	For non-regulated territories		
Exhaust temperature °C (max)	500		
Max exhaust gas flow (m3/min)	2.64		
Max. allowed back pressure (kPa)	7.1		

The above performance data are valid as per the following specs:

- Diesel Fuel is accorg to BS2869 Class A2 or equivalent.
- Lubricating oil is according to Grade SAE 15W-40 API CI4.
- The coolant should be 50% antifreeze and 50% fresh water.

Alternator Technical Data

Make & Model	Leroy Somer TAL040C OR Stamford		
Frequency / No. of poles	60Hz / 4P	Winding pitch	2/3
Ingress protection	IP23	AVR model	R120
Insulation class	H	Overspeed	2250 R.P.M.
Terminals (Optional)	6 (12)	Voltage regulation	$\pm 1\%$
Excitation system	SHUNT	Coolant air flow	0.07 m ³ /s

