

Ratings @ 0.8 PF		Prime Rating	Stand by Rating
Voltage* ¹	Frequency* ²	IMG30* ³	IMG35S* ⁴
230/400 V	50 Hz	32 kVA	35 kVA

Dimensions	
Length	1700 mm
Width	750 mm
Height	1200 mm
Weight	570 Kg

The above ratings represent the generating set capability guaranteed within $\pm 3\%$ at the reference conditions equivalent to those specified in ISO 8528/1 standard.

Notes

1. The applicable voltage range is 380V to 415V for 50Hz applications. For other voltages, please consult factory.

2. This generating set is of fixed speed of 1500 rpm.

3. CT 30 is the prime power rating of the generating set is where a variable load and unlimited hour usage are applied with an average load factor of 80% of the prime rating over each 24-hour period. Noting that a 10% overload is permitted for 1 hour in every 12-hour operation.

4. CT 35S is the standby power rating of the generating set is where a variable load limited to an annual usage up to 500 hours is applied, with 300 hours of which may be continuous running. Noting that no overload is permitted.

Engine Technical Data

Make & Model	CUMMINS X3.3-G1		
Cylinders & Arrangement	4; Vertical in-line		
Bore & Stroke (mm)	91.7 x 127		
Induction system	Naturally Aspirated		
Combustion	Direct injection		
Cycle	4 stroke		
Compression ratio	18.5 : 1		
Cooling System	Water cooled		
Displacement	3.3 liters		
Lube oil capacity	6.5 liters Max		
Coolant capacity	8.6 liters (Engine Only)		
Standard governor	Mechanical Governor		
Engine Speed	1500 rpm		
Fuel Consumption (L/H) @ 100% Load	8.5	@ 50% Load	4.3
Fuel Consumption (L/H) @ 75% Load	6.1	@ 25% Load	2.8
Radiator Cooling Air Flow (m ³ /s)	1.7		
Emissions regulations	Fuel Optimized		
Exhaust temperature °C (max)	550		
Max exhaust gas flow (m ³ /min)	2.3		
Max. allowed back pressure (kPa)	10.2		

The above performance data are valid as per the following specs:

- Diesel Fuel is accorg to BS2869 Class A2 or equivalent.
- Lubricating oil is according to Grade SAE 15W-40 API CI4.
- The coolant should be 50% antifreeze and 50% fresh water.

Alternator Technical Data

Make & Model	Leroy Somer TAL042C		
Frequency / No. of poles	50Hz / 4P	Winding pitch	2/3
Ingress protection	IP23	AVR model	R120 / R180
Insulation class	H	Overspeed	2250 R.P.M.
Terminals (Optional)	6 (12)	Voltage regulation	$\pm 1\%$
Excitation system	SHUNT (AREP+ or PMG)	Coolant air flow	0.1 m ³ /s